

SI-606

Extreme Performance Digital Signage Player

4th Gen. Intel® Core™ Desktop Processor-based Signage Player with AMD Radeon™ E8860 Graphics and Six DP

Signature Book™



Features

- iSMART - for EuP/ErP power saving, auto-scheduler and power resume
- Supports up to 6 displays (DP 1.2) with independent audio output
- Supports 4th Generation Intel® Core™ desktop processor
- Supports 4x DDR3 1600MHz, Max. 32GB
- Flexible VW display configuration setting, Max. resolution: 11520 x 4320
- 2x RS232 serial ports, 2x Mini PCI-E (x1) slots for Wi-Fi, 4G and TV tuner options
- 2x SATA III 2.5" HDD with RAID 1 support
- Compact and rugged design

Specifications

System Mainboard	MBD60E
CPU Type	4th Generation Intel® Core™ i7/i5/i3 and Pentium® Q/C/DC processors, Up to 3.5GHz
CPU Socket	LGA1150
Chipset	Intel® Q87 PCH
Memory	4x 8G DDR3 1600 MHz, Max. 32GB
Graphics	AMD E8860 GPU with 128-bit wide, 2GB GDDR5, 72Gbps 640 Shader processors <ul style="list-style-type: none"> • AMD APP technology, OpenCL™ 1.24, DirectCompute 11.1 • 768 / 48 GFLOPS single- / double-precision peak (600e/4.5Gbps) • Supports AMD Eyefinity technology
LAN	1x Intel® Clarkville I218LM 1x Realtek RTL8111G-CG
Expansion Slots	Dual mPCI-E(x1) slots for Wi-Fi, 4G/LTE, capture card and TV tuner options
I/O Interface	6x DP ports with independent video output 1x DVI-I for console 4x USB 3.0 ports 2x RJ45 for Gigabit LAN 1x DSUB 9pin for RS232 3x Microjack audio connectors for Line-in / Line-out/Mic-in Power LED for power on/off & HDD 1x power button 1x AC power inlet
Watchdog Timer	256 segments, 0, 1, 2...255 (sec/min)
Construction	SGCC
Weight	5.4Kg (11.9lbs)
Chassis Color	Black and white
Storage	1x mSATA 2x SATA III 2.5" HDD Dock (supports RAID 1)
Mounting	Standard system bracket
Dimensions	412mm(W) x 310mm(D) x 47mm(H) 16.22"(W) x 12.2"(D) x 1.85"(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	mSATA: 5 grms / 5~500Hz / random operation
Certification	CE, FCC class B, cULus & CCC
Operating System	Windows XP Win7 32/64-bit, Win8 64-bit, Win8.1 64-bit Win10 64-bit Enterprise, WEC 2013

Ordering Information

SI-606

Signage Player with MBD60E (w/ AMD E8860 for 6x DP), with 4th Gen. Intel® Core™ (DT) i7-4770S processor, 4x 8GB DDR3 DIMM, 2.5" 128GB SSD and 250W PSU.

Dimensions

