



## Features

- Mini-ITX system supports IBASE MI970 Mini-ITX motherboard
- Intel® Core™ i7/i5/i3 QC/DC mobile processors
- Supports 1x RS232/422/485 & 3x RS232
- 2x USB 3.0 ports, 6x USB 2.0 ports
- iSMART- for auto-scheduler and power resume
- 2x Expansion PCI-E(x16) slots with (x8) signal
- Supports 1x 2.5" SATA HDD
- Wall mount kit included

## Specifications

System Mainboard	MI970VF
CPU Type	Intel® Core™ i7/i5/i3/Celeron® QC/DC mobile processors
System Speed	2.7GHz
Memory	2x 2GB DDR3-1600 SO-DIMM, Max. 16GB
Construction	SGCC
Chassis Color	Black
Front Panel External I/O	2x USB 2.0 ports 1x Power LED, 1x HDD LED 1x Power on/off button, 1x reset button
Rear Panel External I/O	1x RS232/422/485 & 3x RS232 1x DVI-I & 1x DVI-D connectors 1x DisplayPort 2x USB 3.0 & 4x USB 2.0 ports 2x RJ45 connectors 1x Audio port (Line-out / Line-in / Mic-in) 2x Expansion PCI-E(x16) slots with (x8) signal
Storage	1x 2.5" HDD/SSD bracket
Power Supply	150W power adaptor Input Voltage: 100V to 240V Input Frequency: 47Hz to 63Hz
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	198mm(W) x 235mm(D) x 120mm(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 1g / 5~500Hz / random operation
Certification	CE / LVD / FCC Class B

## Ordering Information

CMI212-970-3610ME	Chassis with MI970VF Mini-ITX board, w/ Intel® Core™ i5-3610ME(2.7GHz), 4GB DDR3 SO-DIMM, 320GB 2.5" HDD, desktop stand & mounting brackets, 150W power adaptor with power cord (3-pin 10A) (RoHS)
CMI212-970-3120ME	Chassis with MI970VF Mini-ITX board, w/ Intel® Core™ i3-3210ME(2.4GHz), 4GB DDR3 SO-DIMM, 320GB 2.5" HDD, desktop stand & mounting brackets, 150W power adaptor with power cord (3-pin 10A) (RoHS)

## Dimensions and Drawing

